

OMNIKEY® 3121 USB Desktop Reader



USB SMART CARD READER

- **Plug-and-Play** – Designed to facilitate easy device installation with high-quality drivers* for all major PC operating systems
- **Readily Compliant** – Meets all relevant industry standards for smooth integration in PC environment
- **Convenient and Reliable** – Multiple-base mounting options, robust housing, long USB cable
- **Suits Any Application** – Compatible with virtually any smart card and major PC operating system

The OMNIKEY® 3121 is a high-performance, USB smart card reader for desktop use that features multiple-base mounting options and a robust housing. Compliant with all industry standards, this reader is compatible with virtually any contact smart card, operating system and a variety of applications. The

OMNIKEY 3121 is easy to install and well-suited for all contact smart card operations, including single sign-on, online banking or digital signature applications.

* For driver download, please visit www.hidglobal.com/omnikey

FEATURES:

- Meets major standards, including ISO 7816, EMV 2000, Microsoft WHQL, USB CCID, PC / SC, HBCI (Home Banking Computer Interface) and PC-2001 Specification
- Usage within an application is based on standardized interfaces like PC / SC, OCF (Open Card Framework) or CT-API
- Interchangeable standing base options available for both vertical and horizontal configurations, including adhesive attachment that easily mounts to any PC monitor
- USB CCID support makes integration into an existing system the easiest ever by connecting host and smart card reader without the need for additional drivers
- All major operating systems supported
- Meets GSA FIPS 201 requirements
- Supports high-speed data transmission

SPECIFICATIONS

Base Model Number	OMNIKEY® 3121
Dimensions	3.15" x 2.64" x .11" (80 x 67 x 28 mm)
Mounting Options with Standard Standing Base	Includes adhesive attachment pad and vertical mounting option
Weight	Reader only: approx. 3.88 oz (110 g) Reader with standard standing base: approx. 4.97 oz (141 g)
Base Options	Heavy standing base (vertical and horizontal card insertion): available on request (approx. 3.46 oz / 98 g) Jumbo standing base (vertical and horizontal card insertion): available on request (approx. 15.34 oz / 435 g)
Power Supply	Bus powered
Operating Temperature	32-131° F (0-55° C)
Operating Humidity	10-90% rH
HOST INTERFACE	
Host Interface	USB 2.0 CCID ¹ (also compliant with USB 1.1)
Transmission Speed	12 Mbps (USB 2.0 full speed)
SMART CARD INTERFACE	
Standards	ISO 7816 & EMV ² 2000 Level 1
Protocols	T=0, T=1, 2-wire: SLE 4432/42 (S=10); 3-wire: SLE 4418/28 (S=9), I ² C (S=8)
Card Size	ID-1 (full size)
Smart Card Interface Speed	420 Kbps (when supported by card)
Smart Card Clock Frequency	Up to 8 MHz
Supported Card Types	5V, 3V and 1.8V Smart Cards, ISO 7816 Class A, B and C
Power to Smart Card	60 mA
Smart Card Detection	Movement detection with auto power-off / Automatic detection of smart card type / Short circuit and thermal protection
8-Pin Handling	C4 / C8 supported
Supported APIs	PC / SC driver (ready for 2.01), CT-API (on top of PC / SC), Synchronous-API (on top of PC / SC), OCF (on top of PC / SC)
PC / SC Driver Support	Windows® XP/Vista/7/8 (32 bit / 64 bit) Windows Server 2003/2008 (32 bit / 64 bit), 2008R2 (64 bit) Windows CE 4.2/5/6/7 (depending on hardware) Linux®, Mac® OS X and Android™
Embedded Technology	OMNIKEY® Smart@Link Chipset
Status Indicator	Dual-color LED
Reader Board	Also available as PCB
Color	Two-tone gray
Options	Customer-specific logo, label and colors: available upon request
Composition	ABS
Connector Cable	70.9" (180 cm)
Durability	100,000 insertions (200,000 insertions with Landing Contacts version)
Meantime Between Failure (MTBF)	500,000 hours
Compliance / Certification	Microsoft® WHQL ³ , EMV ² 2000 Level 1, ISO 7816, HBCI ⁴ , USB 2.0 (USB 1.1 compatible), CCID ¹ , GSA FIPS 201 approved product list
Safety / Environmental	CE, WEEE, FCC, UL, VCCI, MIC, RoHS
Warranty	Two-year manufacturer's warranty. (For drivers, see complete lifetime support policy.)

1 = Chip Card Interface Device, 2 = Europay® MasterCard® Visa®, 3 = Windows® Hardware Quality Lab, 4 = Home Banking Computer Interface

North America: +1 949 732 2000
Toll Free: 1 800 237 7769
Europe, Middle East, Africa: +44 1440 714 850
Asia Pacific: +852 3160 9800
Latin America: +52 55 5081 1650

hidglobal.com

ASSA ABLOY

An ASSA ABLOY Group brand

© 2011-2013 HID Global Corporation/ASSA ABLOY AB. All rights reserved. HID, HID Global, the HID Blue Brick logo, the Chain Design and OMNIKEY are trademarks or registered trademarks of HID Global or its licensor(s)/supplier(s) in the US and other countries and may not be used without permission. All other trademarks, service marks, and product or service names are trademarks or registered trademarks of their respective owners.
2013-09-12-omnikey-3121-usb-desktop-reader-ds-en PLT#-00318